



Connects2 Vision

User Manual

CAM-PE4/CAM-CT3/CAM-FT4/CAM-TY11

Replacement High Level Third Brake Light Reversing Camera

CAM-PE4 - Peugeot Expert 2007 - 2016

CAM-CT3 - Citroen Jumpy/Dispatch 2007 - 2016

CAM-FT4 - Fiat Scudo 2007 - 2016

CAM-TY11 - Toyota Proace 2013 - 2016

PRODUCT FEATURES:

Image Sensor: 1/3" CMOS

TV Lines: 700

Resolution: 500 x 582

Minimum Illumination: 0 Lux

TV System: PAL

Waterproof Rating: IP69K

Viewing Angle: 120 Degrees

Infra-Red LED's: Yes

Enhanced Performance In Low Light: Yes

Operating Voltage: 12V DC (Negative Ground)

Current Consumption: 45-141mA @ 13.8V

Operating Temperature: -30 Degrees C to +70 Degrees C

DISCLAIMER:

Prior to Installation

Read the manual prior to installation. Technical knowledge is necessary for installation. Please ensure you use the correct tools to avoid damage to the vehicle or product.

Connects2 can not be held responsible for the installation of this product.

Technical Support

Connects2 want to provide a fast and suitable resolution should you encounter any technical issues. With this in mind, when contacting Connects2, try to provide as much information as possible. This will speed up the process and help us to help you.

Please use our dedicated online technical support centre: support.connects2.com

www.c2vision-eu.com

- Camera with 35cm cable to Male 4pin camera connector
- 10m Male to Female 4pin extension cable
- Instructions

INSTALLATION

1. Remove the factory installed third brake light from the vehicle and unplug the connection cable.
2. Connect the new combined brake light/camera assembly to the brake light connector and test to ensure correct brake light operation.
3. Connect the fixed camera cable coming from the new assembly to the connection provided on the extension cable and fit the light/camera to the vehicle in place of the factory light that you have removed, taking care not to trap any cables.
4. Connect the Black wire to a suitable ground and connect the Red wire to the reversing light circuit or an interface which provides a reverse signal.
5. Connect the extension cable to the display screen and ensure that the image is displayed correctly.



Subscribe to our YouTube Channel for installation guides and tips... www.youtube.com/connects2