

CT23FT31

Double/Single DIN Fitting Kit

for Fiat Vehicles



IN THE KIT

- Double DIN Fascia Panel
- Radio Brackets
- 6x Screws

APPLICATION

Note: Application data is subject to change at any time

Fiat 500 (Facelift)

2015 - 2021

Note: this fascia is to be used in vehicles with standard Uconnect Radios, not with the Uconnect 7" Navigation variant.

FEATURES _____

- Allows for the installation of a double/single DIN aftermarket stereo
- · Includes mounting brackets and accessories
- Finished in black to match vehicle dashboard

DISCLAIMER

The information provided in this document is subject to change without notice due to manufacturer changes and/or improvements to the product/s. This instruction manual is based on documented data and research. The manufacturer of this product cannot be held responsible for any changes made to the vehicle by the manufacturer or damages that may occur through the installation of this product in accordance with the steps outlined herein.

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are used during the installation to avoid damage to the vehicle or product. **Connects2 can not be held responsible for the installation of this product.**

INSTALLATION GUIDE

DASH DISASSEMBLY



To begin, use a panel removal tool to unclip the climate control button panel. Be careful not to damage the surrounding trim.

2.



Once the climate control button panel is out of the way, proceed to undo the 2x torx screws located at the top of the aperture.

3.



Now open the glovebox, within the lip on the far side nearest to the passenger side door will be a recessed torx screw. Once this screw has been undone, proceed to fully remove the dashboard trim by means of a panel removal tool, disconnecting the button panel in the process.

INSTALLATION GUIDE

DASH DISASSEMBLY

4.



With the dashboard trim panel out of the way, proceed to undo the 4x highlighted torx screws that surround the main fascia trim. Once free, pull upwards away from the dash.

5.





When the main fascia trim has been removed, undo the 4x screws found on either side of the main unit and proceed to pull it out of the dash whilst disconnecting all of the wiring.

FASCIA ASSEMBLY

6.



Take the brackets that come with the kit and affix them to the relevant side of the new stereo using the screws that come in the kit. When loosely attached, test fit into the dashboard to gauge the correct depth.

INSTALLATION GUIDE

KIT ASSEMBLY

6.



With the brackets aligned correctly, slot the unit into the dashboard and place the new fascia panel into the dashboard. Once happy with the fitment, screw into place using the pre-existing screws.